

Quick Reference of Common Exterior Systems

10.30

1/1 pages
November
2025

Common Exterior Systems		1 st COAT	2 nd COAT	3 rd COAT	4 th COAT
JOINERY	or or	CETOL HLSe CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL FILTER 7 PLUS CETOL BLX-Pro	CETOL HLSe CETOL FILTER 7 PLUS CETOL BLX-Pro	Recommended for exposed areas
CLADDING	or	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	
FASCIA & GABLES	or	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	
LOUVRES	or	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	
FRONT DOORS GARAGE DOORS	or or	CETOL HLSe CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL FILTER 7 PLUS CETOL BLX-Pro	CETOL HLSe CETOL FILTER 7 PLUS CETOL BLX-Pro	
SOFFITS	or	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	
GATES	or	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	
HANDRAILS	or	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro
PERGOLAS	or	CETOL HLSe CETOL HLSe	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro
SPA/SAUNA/POOL AREAS	or	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	-
SHINGLES		CETOL HLSe	CETOL HLSe	CETOL HLSe	-
DECKING DOOR SILLS	or or	CETOL HLSe CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL DECK or DECK SLIP RESISTANT CETOL BLX-Pro	CETOL HLSe CETOL DECK or DECK SLIP RESISTANT CETOL BLX-Pro	-
OUTDOOR FURNITURE	or	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	CETOL HLSe CETOL BLX-Pro	-

* Cetol Clearcoat should only be used on south and east facing protected aspects

The use of flat sawn timber (crown/arrowhead grain pattern) in high sunshine areas will significantly reduce the lifespan of your coating. Flat sawn, dressed weatherboards should be sanded with 80-100 grit sandpaper to slightly roughen surface and remove mill glaze. Flat sawn timber (particularly cedar) has a much higher tendency to distort than quarter sawn timber. Sorting of quarter sawn timber for use in high sunshine areas prior to fixing or manufacture is recommended by BRANZ in their publication "BRANZ Selecting Timber Guide (August 2004)". Coating lifespan can be significantly reduced when used in elevated, seaside or exposed north facing situations. Dark colours such as ebony will have a shorter maintenance cycle.